

## PR1M4



**Article Number:** 181-00139

**Panel Rivet, PA66, Natural, 1,000/bag**



Download drawing



Download spec sheet

### Base Data

**Local Order Number** PR1M4

**Type** PR1

**Color** Natural (NA)

**Features and Benefits** • Panel rivets are made with nylon material to hold duct securely to the panel without corroding, ensuring longevity. • Panel rivets can be easily inserted with use of a specially designed, long shafted panel rivet tool. • Ergonomic design of the tool ensures effortless use when inserting rivets into deep channels or locations difficult to access.

**Product Description** HellermannTyton panel rivets are one piece drive rivets that provide a fast, economic means of affixing wiring duct. The rivet is inserted into a 3/16" pre-punched hole and the pin is driven into the base, thereby expanding the rivet legs and locking the duct and sub-panel in place. The panel thickness (including the duct thickness) should be a maximum of 3/16".

**Short Description** Panel Rivet, PA66, Natural, 1,000/bag

### Product Dimensions

**Minimum Tensile Strength (Imperial)** 107.0 lbs

**Minimum Tensile Strength (Metric)** 478 N

**Panel Thickness Max. (Imperial)** 0.28 "

**Panel Thickness Min. (Imperial)** 0.15 "

**Mounting Hole Diameter D (Imperial)** 0.2 "

**Mounting Hole Diameter D (Metric)** 5.0 mm

**Diameter Max. (Imperial)** 0.02 "

**Diameter Max. (Metric)** 0.51 mm

### Logistics and Packaging

**Quantity Per** EA

**Package Quantity (Imperial)** 1000.0

**Package Quantity (Metric)** 1000.0

**Carton Quantity** 1000.0

### Material and Specifications

**Material** Polyamide 6.6 (PA66)

**Material Shortcut** PA66

**Flammability** UL94 V2

**Operating Temperature** -40°F to +176°F (-40°C to +80°C)

**ROHS compliant (Article 4 - 1)** Yes

