


Waytek PN	Cable	Color Code	Stud	A	B	C	D	E	F	G	H	Barrel
	Size	Markings	Size	+/- .040"	+/- .020"	+/- .012"	+/- .015"	+/- .030"	MIN	MIN	+/- .012"	OD +/- .012"
36564	4	GRAY J-H	1/4"	1.975	.750	.275	.105	.375	.750	.775	.276	.425
36565	4	GRAY J-H	5/16"	1.975	.750	.275	.105	.375	.750	.775	.336	.425
36566	4	GRAY J-H	3/8"	1.975	.750	.275	.105	.375	.750	.775	.402	.425
36514	1-2	PINK H-H	1/4"	2.125	.807	.374	.105	.400	.910	.800	.276	.512
36515	1-2	PINK H-H	5/16"	2.125	.807	.374	.105	.400	.910	.800	.336	.512
36516	1-2	PINK H-H	3/8"	2.125	.807	.374	.105	.400	.910	.800	.402	.512
36517	1-2	PINK H-H	1/2"	2.125	.807	.374	.105	.400	.910	.800	.525	.512
36524	1/0	BLACK E-A	3/8"	2.400	.866	0.433	.120	.430	.950	.920	.402	.571
36525	1/0	BLACK E-A	1/2"	2.400	.866	0.433	.120	.430	.950	.920	.525	.571
36534	2/0	ORANGE A-C	3/8"	2.440	.921	0.472	.155	.470	.950	1.000	.402	.642
36535	2/0	ORANGE A-C	1/2"	2.440	.921	0.472	.155	.470	.950	1.000	.525	.642
36544	3/0	PURPLE A-B	3/8"	2.480	.984	0.551	.160	.520	1.000	1.045	.402	.709
36545	3/0	PURPLE A-B	1/2"	2.480	.984	0.551	.160	.520	1.000	1.045	.525	.709
36554	4/0	YELLOW A-A	3/8"	2.575	1.100	.630	.160	.550	1.000	1.045	.402	.787
36555	4/0	YELLOW A-A	1/2"	2.575	1.100	.630	.160	.550	1.000	1.045	.525	.787

NOTES:

1. MATERIAL: Annealed copper per ASTM B-152
2. FINISH: Parts shall be free of burrs, sharp edges. Parts will be tin plated per ASTM B-545.
3. DIMENSIONS: All dimensions are in inches unless otherwise specified.



				ID "A"	O.D. "B"	I.D. "C"	BL "D"	OL "E"	TL "F"	TW "E"	TT "F"	"G"
	Cable Size	Stud Size	+/- .010	+/- .010	+/- .010	+/- .030	+/- .060	+/- .060	+/- .030	+/- .010	+/- .030	
36351	4	5/16	0.320	0.415	0.275	0.500	1.680	0.830	0.705	0.110	0.440	No
36352	4	3/8	0.405	0.415	0.275	0.5	1.68	0.83	0.705	0.11	0.44	No
36350	4	1/4	0.260	0.415	0.275	0.500	1.680	0.830	0.550	0.150	0.440	No
36353	2	1/4	0.265	0.525	0.385	0.600	1.865	0.860	0.795	0.130	0.425	No
36354	2	5/16	0.328	0.525	0.385	0.6	1.865	0.86	0.795	0.13	0.425	No
36355	2	3/8	0.405	0.525	0.385	0.6	1.865	0.86	0.795	0.13	0.425	No
36356	2	1/2	0.515	0.525	0.385	0.6	1.865	0.86	0.795	0.13	0.425	No
36357	1/0	3/8	0.405	0.595	0.445	0.85	2.04	0.96	0.86	0.135	0.54	No
36358	1/0	1/2	0.515	0.595	0.445	0.85	2.04	1	0.86	0.135	0.54	Yes
36359	2/0	3/8	0.405	0.655	0.485	0.85	2.4	1	0.925	0.17	0.61	No
36360	2/0	1/2	0.515	0.655	0.485	0.85	2.4	1	0.925	0.17	0.61	No
36361	3/0	3/8	0.405	0.72	0.55	0.85	2.46	1.1	1.03	0.175	0.61	No
36362	3/0	1/2	0.515	0.72	0.55	0.85	2.46	1.1	1.03	0.175	0.61	No
36363	4/0	3/8	0.405	0.79	0.63	0.85	2.47	1.02	1.15	0.18	0.53	No
36364	4/0	1/2	0.515	0.79	0.63	0.85	2.47	1.02	1.15	0.18	0.53	No