

Automotive Cross-Link Wire - SAE J1128 TXL

Waytek Stock No.	Gauge	Colors Available	Standard Put-up (Ft.)	Approx. Weight Lbs. per 1,000'	# of Strands	Strand Size	Nom. OD. (in)	Insul. Thickness (in)
WM22	22	0 thru 9, 11, 12, 15, 16	500, 1000, 3000	4	7	30	0.062	0.016
WM20	20	0 thru 9, 11, 12, 15, 16	500, 1000, 3000, 7500 **	6	7	28	0.07	0.016
WM18	18	0 thru 9, 11, 12, 15, 16	500, 1000, 3000, 6000 *	7	19	30	0.078	0.016
WM16	16	0 thru 9, 11, 12, 15, 16	500, 1000, 2500, 5000 *	10	19	29	0.088	0.016
WM14	14	0 thru 9, 11, 12, 15, 16	500, 1000, 2000, 5000 **	14	19	27	0.103	0.016
WM12	12	0, 2, 4 thru 9, 16	250, 500, 1000, 3000 **	22	19	25	0.128	0.018
WM10	10	0, 2	250, 500, 1000, 2500 **	37	19	23	0.156	0.021
WM8	8	0, 2	250, 500, 1000*, 1500 **	57	19	21	0.191	0.022

*These spools are subject to additional charges | **These spools ship via truck

ORDER BY STOCK NO. AND COLOR

WX18 - 0

Type Color

Final ordering stock number: **WX18-0**
Specify footage needed and put-up requirements.

COLORS

0 - ● BLACK	1 - ● BROWN	2 - ● RED	3 - ● ORANGE
4 - ● YELLOW	5 - ● GREEN	6 - ● BLUE	7 - ● VIOLET
8 - ● GRAY	9 - ○ WHITE	11 - ● TAN	12 - ● PINK
15 - ● LT. GREEN	16 - ● LT. BLUE		

Features:

- Operating Temp.: -59°F (-51°C) - 257°F (125°C)
- Compliances: Chrysler MS-8288 and Ford ESB-M1L123-A (18GA only)
- Resistant to moisture, grease, oil, gasoline, most acids and solvents
- Rated up to 60V
- Ultra-thin wall design

Uncontrolled Document
Last Revision: 02.03.2020