

Automotive Cross-Link Wire - SAE J1128 TXL

Waytek Stock No.	Colors Available	Standard Put-up Ft.	Approx. Weight Lbs./mft.	# of Strands	Strand Size	Nom. Cond. OD	Nom. OD (in)	Min. Avg. Wall (in)	Approx. Cu. Lbs./mft.
WM20	0 thru 9, 12	500, 1000, 3000, 7500	7	7	30	0.038	0.070	0.013	30
WM18	0 thru 11, 12, 15, 16	250, 500, 1000, 3000, 6000	7	19	31	0.048	0.078	0.013	12
WM16	0 thru 11, 12, 15, 16	250, 500, 1000, 3000, 5000	10	19	29	0.056	0.088	0.013	7
WM14	0 thru 11, 12, 15, 16	250, 500, 1000, 3000, 5000	15	19	27	0.069	0.103	0.013	5
WM12	0, 2, 5, 6, 9	250, 500, 1000, 3000	23	19	25	0.088	0.128	0.013	5
WM10	0, 2	250, 500, 1000, 2500	37	19	23	0.108	0.155	0.017	3

Features:

- Bare copper
- Insulation: Cross linked polyethylene (XLPE)
- Operating Temperature: -59°F - 257°F (-51°C - 125°C)
- RoHS and REACH compliant
- Compliances: Ford ESB-M1L123-A, Ford ESB-M1L123-A2, Chrysler MS-8288
- Application: Automotive electrical
- Meets or exceeds SAE J1128-TXL specification
- Resistant to moisture, grease, oil, gasoline, most acids and solvents
- Rated for 60 V