



WAYTEK PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING
	MIN IN (mm)	MAX IN (mm)									
21590, UV BLACK	.187 (4.75mm)	2.06 (52.3mm)	8.700 (220.980mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
21570, NATURAL	.187 (4.75mm)	2.06 (52.3mm)	8.700 (220.980mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
21047, UV BLACK	.187 (4.75mm)	4.0625 (103.187mm)	15.093 (383.362mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
21027, NATURAL	.187 (4.75mm)	4.0625 (103.187mm)	15.093 (383.362mm)	.076 (1.930mm)	.300 (7.620mm)	.490 (12.446mm)	.300 (7.620mm)	.500 (12.700mm)	120 (534)	V-2	AH-2
21016, UV BLACK	.187 (4.75mm)	7.000 (177.800mm)	24.500 (622.300mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
21017, NATURAL	.187 (4.75mm)	7.000 (177.800mm)	24.500 (622.300mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
21004, UV BLACK	.187 (4.75mm)	9.000 (228.600mm)	30.875 (784.225mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2
21003, NATURAL	.187 (4.75mm)	9.000 (228.600mm)	30.875 (784.225mm)	.083 (2.108mm)	.302 (7.670mm)	.492 (12.496mm)	.286 (7.264mm)	.476 (12.090mm)	120 (534)	V-2	AH-2



WAYTEK – 120 LB. (534n)
HEAVY DUTY CABLE TIES

MATERIAL:

NYLON 6/6 POLYAMIDE

SHEET 1 OF 1

REV.: A

DRAWING NO.: 120-A

A	12/22/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	12/22/14	KT	NONE

CONFIDENTIAL PROPERTY OF WAYTEK
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF WAYTEK