


WAYTEK PART NUMBER	BUNDLE DIAMETER		A IN (mm) +/- .125 (3.175mm)	B IN (mm) +/- .005 (.127mm)	C IN (mm) +/- .005 (.127mm)	D IN (mm) +/- .020 (.508mm)	E IN (mm) +/- .020 (.508mm)	F IN (mm) +/- .030 (.762mm)	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING	PLENUM RATING					
	MIN IN (mm)	MAX IN (mm)														
21044C, 21044M, UV BLACK	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
21024C, 21024M, NATURAL	.062 (1.57mm)	1.875 (47.625mm)	7.562 (192.075mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
21045C, UV BLACK	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
21025C, NATURAL	.062 (1.57mm)	3.062 (77.775mm)	11.250 (285.751mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
21046C, UV BLACK	.062 (1.57mm)	4.000 (101.600mm)	14.250 (361.951mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
21026C, NATURAL	.062 (1.57mm)	4.000 (101.600mm)	14.250 (361.951mm)	.052 (1.320mm)	.180 (4.572mm)	.300 (7.620mm)	.215 (5.461mm)	.305 (7.747mm)	50 (222)	V-2	AH-2					
																
										WAYTEK - 50 LB. (222n) STANDARD CABLE TIES		MATERIAL: NYLON 6/6 POLYAMIDE				
										SHEET 1 OF 1		REV.: A		DRAWING NO.: 50-A		
						A	12/22/14	JA	KT	KT	INITIAL RELEASE		DRAWN BY		DATE	
						REV	DATE	BY	CHK	APPROVE	DESCRIPTION		JA		12/22/2014	

CONFIDENTIAL PROPERTY OF WAYTEK
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF WAYTEK