



WAYTEK PART NUMBER	BUNDLE DIAMETER		A	B	C	D	E	F	G	H	I	MIN LOOP TENSILE LBS (n)	ANSI/UL 94 MH FLAMABILITY RATING
	MIN IN (mm)	MAX IN (mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .005 (.127mm)	IN (mm) +/- .020 (.508mm)	IN (mm) +/- .030 (.762mm)	IN (mm) +/- .020 (.508mm)		
21051C, 21051M, UV BLACK	.100 (2.550mm)	1.250 (31.750mm)	5.875 (149.225mm)	.045 (1.143mm)	.138 (3.505mm)	.310 (7.874mm)	.175 (4.445mm)	.175 (4.445mm)	.312 (7.924mm)	.325 (8.255mm)	.046 (1.168mm)	40 (180)	V-2
21031C, 21031M, NATURAL	.100 (2.550mm)	1.250 (31.750mm)	5.875 (149.225mm)	.045 (1.143mm)	.138 (3.505mm)	.310 (7.874mm)	.175 (4.445mm)	.175 (4.445mm)	.312 (7.924mm)	.325 (8.255mm)	.046 (1.168mm)	40 (180)	V-2
21052C, 21052M, UV BLACK	.062 (1.587mm)	1.750 (44.450mm)	8.000 (203.200mm)	.052 (1.320mm)	.177 (4.495mm)	.364 (9.245mm)	.183 (4.668mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2
21032C, 21032M, NATURAL	.062 (1.587mm)	1.750 (44.450mm)	8.000 (203.200mm)	.052 (1.320mm)	.177 (4.495mm)	.364 (9.245mm)	.183 (4.668mm)	.208 (5.283mm)	.361 (9.169mm)	.325 (8.255mm)	.049 (1.244mm)	50 (222)	V-2
21053C, UV BLACK	.062 (1.587mm)	3.00 (76.20mm)	11.500 (292.100mm)	.053 (1.346mm)	.177 (4.495mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2
21033C, NATURAL	.062 (1.587mm)	3.00 (76.20mm)	11.500 (292.100mm)	.053 (1.346mm)	.177 (4.495mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2
21054C, UV BLACK	.062 (1.587mm)	4.00 (101.60mm)	14.500 (368.300mm)	.053 (1.346mm)	.177 (4.495mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2
21034C, NATURAL	.062 (1.587mm)	4.00 (101.60mm)	14.500 (368.300mm)	.053 (1.346mm)	.177 (4.495mm)	.357 (9.067mm)	.179 (4.546mm)	.206 (5.232mm)	.356 (9.042mm)	.324 (8.229mm)	.060 (1.524mm)	50 (222)	V-2
21555, UV BLACK	.187 (4.762mm)	4.062 (103.174mm)	15.750 (400.050mm)	.075 (1.905mm)	.298 (7.569mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	V-2
21545, NATURAL	.187 (4.762mm)	4.062 (103.174mm)	15.750 (400.050mm)	.075 (1.905mm)	.298 (7.569mm)	.513 (13.030mm)	.298 (7.569mm)	.256 (6.502mm)	.510 (12.954mm)	.345 (8.763mm)	.074 (1.879mm)	120 (534)	V-2



WAYTEK - MOUNTING HEAD
CABLE TIES

MATERIAL:

NYLON 6/6 POLYAMIDE

SHEET 1 OF 1

REV.: A

DRAWING NO.: MH-A

A	12/23/14	JA	KT	KT	INITIAL RELEASE	DRAWN BY	DATE	CHECK	SCALE
REV	DATE	BY	CHK	APPROVE	DESCRIPTION	JA	12/23/14	KT	NONE

CONFIDENTIAL PROPERTY OF WAYTEK
THIS DRAWING IS PROVIDED ON A RESTRICTED BASIS AND IS NOT TO BE USED IN ANY WAY DETRIMENTAL TO THE INTERESTS OF WAYTEK