

Single Pole



Description	08098700	08098780 Waytek #44511	08099080 Waytek #44518	08080200 Waytek #44504	2484 Waytek #44242	2484-16 Waytek #44243	2484-A	2484-06	2484-09	2484-02	2484-03
Battery Inputs	1	1	1	1	1	1	1	1	1	1	1
Continuous Rating	100A	150A	150A	150A	200A	175A	175A	175A	175A	175A	175A
Intermittent Rating					125A	800A x 15 sec.	1000A x 15 sec.	1000A x 15 sec.	1000A x 15 sec.	1000A x 15 sec.	1000A x 15 sec.
Voltage	12-24V DC	12-24V DC	12-24V DC	12-24V DC	6V DC; 12V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC
Terminal Size	M8	M10	M10	M10	3/8"-24	3/8"-24	3/8"-24	3/8"-24	3/8"-24	3/8"-24	3/8"-24
Terminal Material	Copper	Copper	Copper	Silver Plated Copper	Copper	Brass	Brass	Brass	Copper	Brass	Brass
Terminal Hardware	Zinc-plated Steel	Brass	Zinc-plated Steel	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass
Sealing	IP4X	IP4X	IP43	IP65				Splashproof			Splashproof
Actuator	Key	Key	Key	Knob	Lever	Lever	Lever	Lever	Lever	Hencol key (83353)	Hencol key (83353)
Removable Key	•	•	•							•	•
Lockout-Tagout					with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit
Notes			■ Weatherproof boot	■ Push-to-off	■ UL listed ■ Continuous Ratings 40A at 6V & 20A at 12V ■ Intermittent Ratings 250Aat 6V & 125A at 12V	■ UL listed ■ Silver contacts	■ Silver contacts	■ Silver contacts ■ O-ring in stem ■ Gasket seal in case		■ Indexing pin ■ Silver contacts	■ Indexing pin ■ Silver contacts ■ O-ring in stem



Description	2484-19	M-284	M-284-A	M-284-01	M-284-02	75908 Waytek #44245	75920 Waytek #44076	75920-05	75920-10	75921-10
Battery Inputs	1	1	1	1	1	1	1	1	1	1
Continuous Rating	175A	175A	175A	175A	175A	300A	300A	300A	300A	300A
Intermittent Rating	1000A x 30 sec.	1000A x 15 sec.	1000A x 15 sec.	800A x 15 sec.	1000A x 15 sec.	2000A x 30 sec.	3000A x 15 sec.	3000A x 15 sec.	3000A x 15 sec.	3000A x 15 sec.
Voltage	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	12V DC	12-36V DC	12-36V DC	12-36V DC	12-36V DC
Terminal Size	3/8"-24	3/8"-24	3/8"-24	3/8"-24	3/8"-24	1/2"-20	3/8"-24	3/8"-24	3/8"-24	M10
Terminal Material	Brass	Copper	Brass	Brass	Brass	Copper	Tin Plated Copper	Tin Plated Copper	Tin Plated Copper	Tin Plated Copper
Terminal Hardware	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Stainless Steel	Stainless Steel
Sealing	Splashproof				Splashproof	Splashproof	IP68*	IP68*	IP68*	IP68*
Actuator	Hencol key (83353)	Chrome Lever	Chrome Lever	Chrome Lever	Lever	Lever	Knob	Knob	Knob	Knob
Removable Key	•									
Lockout-Tagout	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	•	•	•	•
Notes	■ Indexing pin ■ Silver Contacts ■ O-ring in stem ■ Gasket seal in case	■ Extra long mounting stem	■ Silver contacts ■ Extra long mounting stem	■ Silver contacts ■ Ignition protected ■ Extra long mounting stem	■ Silver contacts ■ O-ring in stem ■ Gasket seal in case ■ Extra long mounting stem	■ Indexing pin ■ Gasket seal in case	■ Indexing pin ■ *Thermal cycling followed by immersion (1m)	■ Indexing pin ■ International I/O marks ■ *Thermal cycling followed by immersion (1m)	■ Indexing pin ■ *Thermal cycling followed by immersion (1m)	■ Indexing pin ■ International I/O marks ■ *Thermal cycling followed by immersion (1m)

Single Pole



Description	08098400	08098800	08098881 Waytek #44513	08098882 Waytek #44514	880062 Waytek #44056	880064 Waytek #44058	880154 Waytek #44042	08098900 Waytek #44515	08098980 Waytek #44516	08098981 Waytek #44517
Battery Inputs	1	1	1	1	1	1	1	1	1	1
Continuous Rating	250A	250A	250A	250A	300A (1x 4/0 cable)	300A (1x 4/0 cable)	600A (2x 4/0 cable)	350A	350A	350A
Intermittent Rating	600A x 120 sec.	600A x 120 sec.	600A x 120 sec.	600A x 120 sec.	1250A (1x 4/0 cable) x 30sec.	1250A (1 x 4/0 cable) x 30 sec.	2500A (1 x 4/0 cable) x 30 sec.	1500A x 120 sec.	1500A x 120 sec.	1500A x 120 sec.
Voltage	24V DC	24V DC	24V DC	24V DC	48V DC Max.	48V DC Max.	36V DC Max.	12-24V DC	12-24V DC	12-24V DC
Terminal Size	M10	M10	M10	M10	3/8"-16	3/8"-16	3/8"-16	M12	M12	M12
Terminal Material	Silver Plated Copper	Silver Plated Copper	Silver Plated Copper	Silver Plated Copper	Tin Plated Copper	Tin Plated Copper	Tin Plated Copper	Silver Plated Copper	Silver Plated Copper	Silver Plated Copper
Terminal Hardware	Zinc-plated Steel	Zinc-plated Steel	Zinc-plated Steel	Zinc-plated Steel	Stainless Steel	Stainless Steel	Stainless Steel	Zinc-plated Steel	Zinc-plated Steel	Stainless Steel
Sealing	IP65	IP65	IP65/IP69K	IP65/IP69K			IP67/ IP69K	IP65	IP65	IP65/IP69K
Actuator	Knob	Handle	Handle	Handle	Knob	Knob	Knob	Handle	Handle	Handle
Removable Key		•	•			•	•	•	•	
Lockout-Tagout				•						
Notes			■ Actuator Tether ■ Weatherproof Boot	■ Weatherproof Boot	■ Ignition protected	■ Ignition protected	■ High cranking amps ■ Ignition protected		■ Actuator Tether ■ Weatherproof Boot	■ Weatherproof Boot

Double Pole



Description	75903 Waytek #43921	75904	75904-01 Waytek #43922	75904-02	75904-03	M-290	M-290-01	M-290-05	75912	75907 Waytek #44244	08084300 Waytek #44507	08084400 Waytek #44508	880175 Waytek #44057	M-750 Waytek #44043
Battery Inputs	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Continuous Rating	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A large studs 20A small studs	125A	300A	250A	500A	500A per circuit	310A
Intermittent Rating	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	1000A x 15 sec. (Large studs)	750A x 15 sec.	2000A x 30 sec.	1000A x 2 sec	1500A x 2 sec.	2250A x 30 sec. (2 x 4/0 cables)	500A
Voltage	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	6-36V DC	24V DC	24V DC	12-24V DC	6-36V DC
Terminal Size	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	two 3/8"-24 two 10-32	3/8"-24	two 1/2"-20 two 10-32	M10	M12	M12	3/8"
Terminal Material	Copper/Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Copper	Silver Plated Copper	Silver Plated Copper	Tin Plated Copper	Copper
Terminal Hardware	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Brass	Stainless Steel	Stainless Steel	Stainless Steel	Brass
Sealing							Splashproof		Splashproof		IP67/IP69K	IP67/IP69K	IP67/ IP69K	
Actuator	Chrome Lever	Chrome Lever	Chrome Lever	Hencol key (83353)	Hencol key (83353)	Chrome Lever	Chrome Lever	Chrome Lever	Chrome Lever	Lever	Handle	Handle	Knob	Knob
Removable Key					•						•	•		
Lockout-Tagout	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	with 24505 kit	•	•	•	
Notes			■ Indexing pin	■ Indexing pin	■ Indexing pin	■ Silver contacts ■ Extra long mounting stem	■ Silver contacts ■ O-Ring ■ Extra long mounting stem	■ UL listed ■ Silver contacts ■ Extra long mounting stem	■ Indexing pin ■ O-ring in stem ■ Gasket sealing in case ■ Hencol	■ Indexing pin	■ Weatherproof Boot ■ Silver contacts	■ Weatherproof Boot ■ Silver contacts		■ M-752 w/ alternator field disconnect ■ M-754 w/ pilot light circuit